


SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER	THRIFTY-SORB
CHEMICAL NAME	Montmorillonite Clay, Calcined
CHEMICAL FAMILY	Clay
MATERIAL USE	Oil Absorbent
RESTRICTION ON USE	None Known
MANUFACTURER	EP Minerals, LLC., 9875 Gateway Dr., Reno, NV 89521
TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
EMERGENCY TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
SDS DATE OF PREPARATION	January 28, 2014

SECTION 2: HAZARDS IDENTIFICATION

OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1
HAZARDS NOT OTHERWISE CLASSIFIED	None
LABEL ELEMENTS	<p>DANGER May cause cancer by inhalation. Causes damage to lungs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear eye protection. If exposed or concerned: Get medical advice. Dispose of contents in accordance with local, state and federal regulations.</p> 

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS
Montmorillonite Clay, Calcined (contains 10-15% Crystalline Silica - Quartz)	100%	70892-59-0 14808-60-7

SECTION 4: FIRST AID MEASURES

EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
SKIN	Use moisture renewing lotions if dryness occurs.
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.
INHALATION	Remove to fresh air. Blow nose to evacuate dust.
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.

MATERIAL NAME	THRIFTY-SORB			Page 2 of 4
SECTION 5: FIRE FIGHTING MEASURES				
EXTINGUISHING MEDIA	Not applicable, the material is not combustible.			
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.			
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.			
SECTION 6: ACCIDENTAL RELEASE MEASURES				
PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.			
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.			
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage or wet sweep. Avoid creating airborne dust. Place in a container for use or disposal.			
SECTION 7: HANDLING AND STORAGE				
PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Repair or dispose of broken bags. Observe all label precautions and warnings. Flammable or hazardous substances may retain such characteristics after absorption. Care should be taken to store and dispose of waste material in accordance with instructions of manufacturer of substance absorbed and applicable laws. Do not use with hydrofluoric acid or concentrated caustic solutions.			
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Store product separately from feed, food, pesticides and fertilizers so that cross contaminations does not occur. Do not store near hydrofluoric acid or concentrated caustic solutions.			
SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION				
EXPOSURE GUIDELINES:				
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL
Montmorillonite Clay, Calcined (as Particulates not otherwise classified)	5 mg/m³ respirable dust 15 mg/m³ total dust	None Established	5 mg/m³ respirable dust 15 mg/m³ total dust	None Established
Crystalline Silica (Quartz)	30 mg/m³ % SiO₂+2 total dust 10 mg/m³ % SiO₂+2 Respirable dust	0.025 mg/ m³ Respirable dust	30 mg/m³ % SiO₂+2 total dust 10 mg/m³ % SiO₂+2 Respirable dust	0.05 mg/ m³ Respirable dust
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.			
PERSONAL PROTECTIVE EQUIPMENT:				
EYE / FACE PROTECTION	Goggles to protect from dust			
SKIN PROTECTION	No special equipment is needed.			
RESPIRATORY PROTECTION	Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half-mask respirator with a N95 dust filter or a single use dust mask rated N95. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two hundred (200) times the PEL use a power air-purifying (positive pressure) respirator with a replaceable N95 filter. If dust concentration is greater than two hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.			
GENERAL HYGIENE	Avoid breathing dust. Avoid contact with eyes. Wash hands after handling and before eating or drinking.			

MATERIAL NAME	THRIFTY-SORB	Page 3 of 4
---------------	--------------	-------------

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE, COLOR	Tan to gray	ODOR	Odorless
PHYSICAL STATE	Solid	ODOR THRESHOLD	Not applicable
VAPOR PRESSURE	Not applicable	VAPOR DENSITY	Not applicable
BOILING POINT	Not applicable	MELTING POINT	Unknown
FLASH POINT	Not applicable	pH (10% SUSPENSION)	Unknown
FLAMMABILITY LIMITS	Not applicable	EVAPORATION RATE	Not applicable
DECOMPOSITION TEMPERATURE	Unknown	SPEC. GRAVITY / RELATIVE DENSITY	2.2
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT – n-OCTANOL/WATER	Not applicable
FLAMMABILITY (solid/gas)	Not applicable	SOLUBILITY – WATER	< 1.0%
		VISCOSITY	Not applicable

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	Material is not reactive.
CHEMICAL STABILITY	Material is stable.
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.
CONDITIONS TO AVOID	Not applicable
INCOMPATIBLE MATERIALS	Unsaturated organic compounds, such as turpentine and vegetable oil, hydrofluoric acid and concentrated caustic solutions may react violently with the product.
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS	
Likely Routes of Exposure	See below
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.
INGESTION	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.
CHRONIC EFFECTS	This product contains naturally occurring crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.
CARCINOGENICITY	This natural product is composed predominantly of clay, but contains some crystalline silica. Respirable crystalline silica (quartz) is classified by IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.
NTP	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
IARC	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
NUMERICAL MEASURES OF TOXICITY	No data available

MATERIAL NAME		THRIFTY-SORB		Page 4 of 4						
CORROSIVENESS, SENSITIZATION, IRRITANCY		Not applicable								
REPRODUCTIVE TOXICITY		Not available								
TERATOGENICITY, MUTAGENICITY		Not available								
SECTION 12: ECOLOGICAL INFORMATION										
ECOTOXICITY:		No toxicity is expected								
PERSISTENCE AND DEGRADABILITY		Non-biodegradable, inert.								
BIOACCUMULATIVE POTENTIAL		Little potential for bioaccumulation								
MOBILITY IN SOIL		No mobility								
OTHER ADVERSE EFFECTS		None known								
SECTION 13: DISPOSAL CONSIDERATIONS										
WASTE DISPOSAL		If this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).								
PACKAGING DISPOSAL		Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.								
SECTION 14: TRANSPORT INFORMATION										
BASIC SHIPPING INFORMATION		DOT shipping classification 55 (no restrictions). Technical name is "Calcined Clay".								
ADDITIONAL INFORMATION		No special requirements or placarding necessary.								
SECTION 15: REGULATORY INFORMATION										
U.S. FEDERAL:										
TSCA		Montmorillonite and Quartz appear on the EPA TSCA inventory list.								
CERCLA		Montmorillonite is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.								
SARA TITLE III		Not listed.								
California Proposition 65:		This product contains crystalline silica, a chemical known to the State of California to cause cancer.								
INTERNATIONAL:										
WHMIS Classification		Class D-2-A								
WHMIS Ingredient Disclosure List		Silica, crystalline, quartz								
SECTION 16: OTHER INFORMATION										
				<table border="1"> <tr> <td rowspan="4">HMIS</td> <td>0* Health</td> </tr> <tr> <td>0 Flammability</td> </tr> <tr> <td>0 Reactivity</td> </tr> <tr> <td>E Protective Equipment</td> </tr> </table>		HMIS	0* Health	0 Flammability	0 Reactivity	E Protective Equipment
HMIS	0* Health									
	0 Flammability									
	0 Reactivity									
	E Protective Equipment									
ORIGINAL ISSUE DATE		January 14, 2014								
REVISION DATE		October 28, 2014								
REVISION NO.		2								

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.



9785 GATEWAY DR
Reno, NV 89521
(775) 824-7600

Order Confirmation

Customer No: M65012-01
Order Date: 04/20/2016
Order No: C213888
PO No: 144041-1
Your Reference: OK
Our Reference: Kathleen Down
Salesman: Mike Elliott

Origination Site: MIDDLETON

Freight Desc: DRY VAN
No of cntrs: 0
Region Desc:

Net Weight: 42000 lbs.
Gross Weight: 42025 lbs.
Ship Via: RYT

Delivery Address 01
BAUMANN PAPER CO.
1601 BAUMANN DR.
LEXINGTON, KY 40512
UNITED STATES

Customer Address

BAUMANN PAPER CO
ATTN: ACCOUNTS PAYABLE
P O BOX 13022
LEXINGTON KY 40512

Domestic Delivery Terms: PREPAY & ADD

Estimated Ship Date: 04/25/2016
***** Shipments arranged by EP Minerals may ship up to 7 days prior to Estimated Ship Date. *****

Payment Terms: 30 Days Net

Ocean Delivery Terms:

Routing Notes:

Doc Cutoff Date:

Last Load Date:

Part No:			Sales Qty						
Del No	Líne No	Part No Desc:	Price Qty	UOM	Sales Unit	Discount	Price Total		
1	1	<u>7941</u>	<u>1,000.0000</u>	40 LB	188.5000				
		SAFE-T-SORB (FFS) 40 50GMA	20.0000	NTON			USD	3,770.00	
		Per Bag Price:	3.7700						
1	3	PALLETS	21.0000	EA					
		PALLETS	21.0000	EA					
1	4	STRETCHWRAP	21.0000	EA					
		STRETCHWRAP	21.0000	EA					
1	5	<u>8440</u>	<u>50.0000</u>	40 LB	172.3900				
		THRIFTY-SORB (FFS) 40 50GMA	1.0000	NTON			USD	172.39	
		Per Bag Price:	3.4478						
							Subtotal USD	\$3,942.39	
							GRAND TOTAL USD	\$3,942.39	

CINDY BREWER (P) 859-252-8891 (F) 859-254-0579 EMAIL: CJBREWER@BAUMANNPAPER.COM

FREIGHT CHARGES ARE AN ESTIMATE ONLY AND MAY VARY UPON SHIPMENT.

CUSTOMER ARRANGED SHIPMENTS: PLEASE REFERENCE OUR CUSTOMER ARRANGED TRANSPORTATION POLICY ON OUR WEBSITE AT <http://epminerals.com/customer-center>. PLEASE ENSURE YOUR CARRIER IS INFORMED AND P/U APPTS ARE MADE.

PLEASE LOOK OVER THIS CONFIRMATION CAREFULLY AND ADVISE OF ANY ERRORS AS SOON AS POSSIBLE. THANK YOU FOR YOUR ORDER. WE APPRECIATE YOUR BUSINESS.

SURVEY: At EP Minerals we are committed to providing you with amazing service and incredible minerals every day. We want to continually improve on our service, quality and our products. We want your feedback to help us do that as well as to serve you better. Please take just a few moments to give us your feedback today. Thank you. Please find survey at:
<https://www.surveymonkey.com/r/TRZW3QX>



9785 GATEWAY DR
Reno, NV 89521
(775) 824-7600

Order Confirmation

Customer No: M65012-01
Order Date: 04/20/2016
Order No: C213888
PO No: 144041-1
Your Reference: OK
Our Reference: Kathleen Down
Salesman: Mike Elliott

Origination Site: MIDDLETON

Freight Desc: DRY VAN
No of cntrs:
Forwarder:

Net Weight: 42000 lbs.
Region Desc:
Ship Via: RYT

Delivery Address
BAUMANN PAPER CO.
1601 BAUMANN DR.
LEXINGTON, KY 40512
UNITED STATES

Customer Address

BAUMANN PAPER CO
ATTN: ACCOUNTS PAYABLE
P O BOX 13022
LEXINGTON KY 40512

Domestic Delivery Terms: PREPAY & ADD

Ocean Delivery Terms:

Estimated Ship Date: 04/25/2016

Routing Notes:

***** Shipments arranged by EP Minerals may ship up
to 7 days prior to Estimated Ship Date. *****

Payment Terms: 30 Days Net

Doc Cutoff Date:

Last Load Date:

Part No:			Sales Qty				
Del No	Line No	Part No Desc:	Price Qty	UOM	Sales Unit	Discount	Price Total

EP Minerals expressly rejects any additional or Inconsistent terms in any purchase offer, counter-offer, or other document from Buyer. EP Minerals Terms and Conditions supersede all other documents. For a copy of the terms and conditions governing the sale of the product described in this document, refer to <http://epminerals.com/library/290/94/EPM-Product-Purchases-Terms-Conditions>. The terms and conditions are hereby incorporated by reference as if included in their entirety, and are made a part of this agreement, except as modified on this document. Alternatively, you can contact EP Minerals LLC directly for a copy.